

A Smarter Way for Your Broadband Life

Huawei HS8145V, an intelligent routing-type ONT



HUAWEI

Device Parameters

| | |
|---------------------------|---|
| Dimensions (L x W x H) | 250mm x 120Mmm x 35mm |
| Weight | About 1500 g |
| Operating temperature | 0°C to +40°C |
| Operating humidity | 5% RH to 95% RH (non-condensing) |
| Power adapter input | 100–240 V AC, 50–60 Hz |
| System power supply | 11-14 V DC, 1.5A |
| Static power consumption | 8 W |
| Maximum power consumption | 20.5 W |
| Ports | 1POTS+4GE+2.4G/5.G WIFI+1USB |
| Indicators | POWER/PON/LOS/TEL/LAN/2.4G WiFi/5G WiFi/WPS/USB |

Interface Parameters

| | |
|----------------------|--|
| GPON Port | <ul style="list-style-type: none"> • Class B+ • Receiver sensitivity: -27 dBm • Wavelengths: US 1310 nm, DS 1490 nm • WBF • Flexible mapping between GEM Port and TCONT • GPON: consistent with the SN or password authentication defined in G.984.3 • Bi-directional FEC • SR-DBA and NSR-DBA |
| Ethernet Port | <ul style="list-style-type: none"> • Ethernet port-based VLAN tags and tag removal • 1:1 VLAN, N:1 VLAN, or VLAN transparent transmission • QinQ VLAN • Limit on the number of learned MAC addresses • MAC address learning |
| POTS Port | <ul style="list-style-type: none"> • Maximum REN: 4 • G.711A/μ, G.729a/b and G.722 encoding/decoding • T.30/T.38/G.711 fax mode • DTMF • Emergency calls (with the SIP protocol) |
| USB Port | <ul style="list-style-type: none"> • USB2.0 • FTP-based network storage • File/Print sharing based on SAMBA • DLNA DMS/UPnP AV (media server) |
| WLAN | <ul style="list-style-type: none"> • IEEE 802.11 b/g/n (2.4G) • IEEE 802.11 a/n/ac (5G) • 2 × 2 MIMO (2.4G); 2 × 2 MIMO (5G) • Antenna gain: 3 dBi • WMM/Multiple SSIDs/WPS • 2.4G/5G concurrent • Air interface rate: 300 Mbit/s (2.4G) 1300 Mbit/s (5G) |

Product Function

Smart interconnection

- Smart Wi-Fi coverage
- SIP/H.248 auto-negotiation
- Any port any service
- Parental control
- L2/L3(IPv4) forwarding: 1G uplink, 2G downlink

Smart service

- Smart Wi-Fi sharing:
Portal/802.1x authentication
SoftGRE-based sharing
Association of one account with two POTS ports

Smart O&M

- IPTV video quality diagnosis
- Variable-length OMCI messages
- Active/Passive rogue ONT detection and isolation
- Call emulation, and circuit test and loop-line test
- PPPoE/DHCP simulation testing
- WLAN emulation

Layer 3 Features

- PPPoE/Static IP/DHCP
- NAT/NAPT
- Port forwarding
- ALG, UPnP
- DDNS/DNS server/DNS client
- IPv6/IPv4 dual stack, DS-Lite and IPv6 SPI
- Static/Default routes
- Multiple services on one WAN port

Multicast

- IGMP v2/v3 proxy(V300R015C00)/snooping
- MLD v1/v2 snooping
- Multicast services through Wi-Fi

QoS

- Ethernet port rate limitation
- 802.1p priority
- SP/WRR/SP+WRR
- Broadcast packet rate limitation

Security

- SPI firewall
- Filtering based on MAC/IP/URL addresses

Common O&M

- OMCI/Web UI/TR069
- Dual-system software backup and rollback

Power Saving

- Dynamic power saving
- Indicator power saving
- Scheduled Wi-Fi shutdown
- COCv5

HUAWEI